IN THE CLAIMS

Please amend claims 1 and 6, all claims reading as follows:

31/

- 1. (Currently Amended) In a data processing system having a system bus and having a processor with a level one cache memory responsively coupled to a level two cache memory which is responsively coupled via said system bus to a level three cache memory which is directly coupled to at least one memory storage unit and having a circuit for directly SNOOPing said system bus, the improvement comprising:
- a. First logic which invalidates a corresponding level one cache memory location in response to either a non-local memory write or write ownership request.
- 2. (Original) A data processing system according to claim

 1 further comprising second logic which inhibits said first logic

 from invalidating for mode 3 requests without ownership.
- 3. (Original) A data processing system according to claim 1 further comprising:
- a. Third logic which invalidates said corresponding cache memory location in response to a SNOOP hit.

- 4. (Original) A data processing system according to claim 3 further comprising:
- a. Fourth logic which retrieves and records data in response to a level one cache memory read miss and a level two cache memory read miss.
- 5. (Original) A data processing system according to claim

 1 further comprising:
- a. Fifth logic which determines when said level two cache memory generates a parity error and which in response invalidates said corresponding level one cache memory location.
- 6. (Currently Amended) A data processing system comprising:
 - a. A processor having a level one cache memory;
- b. A level two cache memory responsively coupled to said level one cache memory;
 - c. a system bus;
 - d. A memory storage unit;
 - e. A level three cache memory responsively coupled to said level two cache memory via said system bus and responsively coupled to said memory storage unit; and

- \underline{e} \underline{f} . A first circuit which invalidates a corresponding portion of said level one cache memory in response to a level one cache memory write hit and a level two cache memory write.
- 7. (Original) A data processing system according to claim 6 further comprising:
- a. A second circuit which inhibits said first circuit from said invalidating in response to a mode 3 lack of ownership.
- 8. (Previously Amended) A data processing system according to claim 6 further comprising:
 - a. A third circuit which SNOOPs said system memory bus; and
- b. A fourth circuit which invalidates said corresponding portion of said level one cache memory in response to a SNOOP hit.
- 9. (Original) A data processing system according to claim 6 further comprising:
- a. A fifth circuit which retrieves and records data in response to a level one cache memory read miss and a level two cache memory read miss.
- 10. (Original) A data processing system according to claim 6 further comprising:

- a. A sixth circuit which detects parity errors of said level two cache memory and invalidates said corresponding portion of said level one cache memory in response to said detected parity error.
- 11. (Original) A method of maintaining validity of data within a level one cache memory of a processor responsively coupled to a level two cache memory which is responsively coupled to a system memory bus comprising:
 - a. Formulating a write memory request;
- b. First experiencing a level one cache memory miss in response to said write memory request;
- c. Second experiencing a level two cache memory hit in response to said first experiencing step; and
- d. Invalidating a portion of said level one cache memory corresponding to said write memory request in response to said second experiencing step.
- 12. (Original) A method according to claim 11 further comprising:
- a. Inhibiting said invalidating step if said write memory request is mode 3 lacking ownership.

- 13. (Original) A method according to claim 11 further comprising:
 - a. SNOOPing said system memory bus; and
- b. Invalidating said portion of said level one cache memory if said SNOOPing step identifies data corresponding to said write memory request.
- 14. (Original) A method according to claim 11 further comprising:
 - a. Formulating a read memory request;
- b. Third experiencing a level one cache memory read miss; and
- c. Retrieving and recording data corresponding to said read memory request.
- 15. (Original) A method according to claim 11 further comprising:
- a. Determining whether a reference to said level two cache memory has a parity error; and
- b. Invalidate said portion of said level one cache memory in response to said determining said parity error.
 - 16. (Original) An apparatus comprising:
 - a. Means for executing program instructions;

- b. Means responsively coupled to said executing means for level one caching data;
- c. Means responsively coupled to said executing means and said level one caching means for accessing a data element if said executing means requires accessing of said data element and said level one caching means does not contain said data element;
- d. Means responsively coupled to said requesting means for level two caching data; and
- e. Means responsively coupled to said level one caching means for invalidating said data element if said data element is a write data element located within said level two caching means.
- 17. (Original) An apparatus according to claim 16 further comprising:
- a. Means responsively coupled to said invalidating means for inhibiting said invalidating if said data element is mode 3 without ownership.
- 18. (Original) An apparatus according to claim 16 further comprising:
- a. Means responsively coupled to said level two caching means for bussing system memory data;
- b. Means responsively coupled to said bussing means for SNOOPing said bussing means; and

- c. Means responsively coupled to said SNOOPing means for invalidating said data element if said SNOOPing means locates a corresponding data element and said data element is a write data element.
- 19. (Original) An apparatus according to claim 16 further comprising:
- a. Means responsively coupled to said level two caching means for retrieving and record said data element if said data element is a read data element and said level two caching means experiences a miss.
- 20. (Original) An apparatus according to claim 16 further comprising:
- a. Means responsively coupled to said level two caching means for detecting a parity error; and
- b. Means responsively coupled to said level one caching means and said detecting means for invalidating said data element if said detecting means detects said parity error.